

MEHTA SANGHVI & COMPANY

WELDING FOR BUILDING NATION MSC MAKE CUTTING, BEVELLING, WELDING EQUIPMENTS



World Biggest Company for Inverter Welding Machines



Features :

- 1. Smooth Arc-Striking With HF Control.
- 2. Quality Narrow Cutting and Excellent Travel Speed.
- 3. Cutting Accessories With Competitive Price & Performance.
- 4. Recommended Thickness : 10mm (Carbon Steel)
- 5.Wide Range for Input Voltage : 220V + 15%
- 6. Super Portable & Energy Saving.

Features :

- 1. Smooth Arc-Striking With HF Control.
- 2. Quality Narrow Cutting & Excellent Travel Speed.
- 3. Cutting Accessories With Competitive Price & Performance.
- 4. Recommance Thickness : 15mm (Carbon Steel).
- 5. Pilot-Arc to Extend the Durability of Consumables.
- 6. Wide Range for Input Voltage : 380V +15%
- 7. Portable & Energy Saving.
- 8. With Advanced Single IGBT Technology.





Features :

- 1. Smooth Arc-Striking With HF Control.
- 2. Quality Narrow Cutting & Excellent Travel Speed.
- 3. Cutting Accessories With Competitive Price & Performance.
- 4. Recommened Thickness : 30mm (Carbon Steel).
- 5. Pilot-Arc to Extend the Durability of Consumables.
- 6. Wide Range for Input Voltage : 380V <u>+</u>15%
- 7. Energy Saving.



Features :

- 1. Smooth Arc-Striking With HF Control.
- 2. Quality Narrow Cutting and Excellent Travel Speed.
- 3. Cutting Accessories With Competitive Price & Performance.
- 4. Recommended Thickness : 40mm (Carbon steel).
- 5. Pilot-Arc to Extend the Durability of Consumables.
- 6. Wide Range for Input Voltage : $380V \pm 15\%$
- 7. Energy Saving.



CUT 60G



MEHTA SANGHVI & COMPANY

WELDING FOR BUILDING NATION

MSC MAKE CUTTING, BEVELLING, WELDING EQUIPMENTS

21, Gokul Indl. Est., Plot No.150, Marol, M. V. Road, Andheri (E), Mumbai -400 059. **Tel. :** +91-22-2859 2847, 2852 3395, 2852 8925 **E-mail :** mehtasanghvi.k@gmail. com / service.mehtasanghvi.k@gmail.com

Website : www.mehtasanghvi.com I www.orbitalweldingandcutting.com I www.mehtasanghvi.net I www.weldingaccessoriesindia.com

MACHINE TYPE	CUT 40	CUT 60G	CUT 100IJ	CUT 160I
Main Voltage (+/-10%)	AC220V <u>+</u> 15% 1P	AC380V <u>+</u> 15% 3P	AC380V <u>+</u> 15% 3P	AC380V <u>+</u> 15% 3P
Rated input power capacity (KVA)	6.6 KVA	7.8KVA	15.1KVA	29KVA
Input Voltage Frequency (Hz)	50 / 60	50 / 60	50 / 60	50 / 60
Output Current Range (A)	15-40A	20-60A	20-100A	20-160A
Input Amp. (A)	30A	12.3A	23.1A	44A
Duty Cycle (%)	60%	60%	60%	60%
Efficiency (%)	80%	85%	85%	85%
Power Factor	0.73	0.93	0.93	0.93
Protection Class	IP21	IP21	IP21	IP21
Weight (Kgs)	9kg	24.5kg	36.5kg	60kg
Dimensions (mm)	395X153X301(mm)	485X234X425(mm)	550X280X545(mm)	670X320X640(mm)

PLASMA TORCH



PLASMA SPARES





PLASMA SPARES

